



SCC-251KBIA

SANTEC HD-CVI Full HD IR bullet camera
2,8 - 11 mm mot. vario lens, IP-44

PRODUCT DESCRIPTION

► Application:

SANTEC HD-CVI day/night bullet camera for INDOOR applications, IP-44 classification. Due to the built-in IR-LEDs (range: up to 30m) and the motorised vario lens (2.8 - 11mm), the camera is suitable for day as well as for night applications. The camera has an excellent resolution of 1080p at 25 fps. The camera comes with a wall bracket with integrated cable management.

► Technical specifications:

Type	Day/Night bullet camera
Video norm	HD-CVI, PAL
Sensor	1/2.9"
Sensor type	1/2.9" CMOS
Horizontal resolution (TVL)	1080p / 720p
Effective pixel	1920x1080
Signal processing	Digital (DSP)
Synchronisation	Intern
Lens type	Motorized DC vario lens
Focal length	2.8 - 11 mm / F1.2
Angle of view (horizontal)	90° - 28°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.05 / 0.0 lux
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	3DNR
Shutter (sec.)	1/3 - 1/100,000
Video output	BNC, 75 Ohm 1 Vpp

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Classification	IP-44
Vandal-proof	No
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR range (m)	up to 20
IR wave length	850
Voltage	12 V DC / 24 V AC
Power consumption (watt)	7.7
Operating temperature (°C)	-30 to +40
Rel. humidity (%)	30 - 90
Dimensions DxT (mm)	193 x 69 x 90
Weight	720 g
Identifier	CE, RoHS
Specials	Coaxtransmission up to 700m

► Note:

The range of the built-in IR-LEDs strongly depend on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring
JB-500	SANTEC Junction Box for cameras for WB-HDH (WB-HDHW) & SANTEC cameras
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter