



### HDCVI-2105

CVI auf HDMI Konverter  
 Weitere Ausgänge: VGA, FBAS und HD-CVI

## PRODUCT DESCRIPTION

#### ► Application:

This converter is converting the signal from a HD-CCTV camera to the HDMI, VGA and CVBS format.

#### ► Technical specifications:

Type	HD-CVI to HDMI Converter
Input	1x HD-CVI (BNC)
Output	1x HDMI, 1x VGA, 1x CVBS, 1x HD-CVI
RS-485 interface	Yes, 1x
Impedance (Ohm)	75
Voltage	12 V DC
Power consumption (watt)	15
Dimensions WxHxD (mm)	162x30x136,4
Weight	200 g
Identifier	CE
Installation	Wall mount
Operating temperature (°C)	-10 to +55
Rel. humidity (%)	10 - 90, non-condensing
Specials	Without power supply

#### ► Note:

Without power supply.

SANTEC BW AG  
 An der Strusbek 31, 22926 Ahrensburg, Germany  
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10  
 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

## ► Recommended Accessories

SCC-20KBIF	SANTEC 1080p HD-CVI IR bullet camera 6 mm fix lens, 12 V DC, IP-66
SCC-221KDNM	SANTEC HD-CVI Full HD dome camera 2,8 - 11 mm, manual vario lens, IP-44
SCC-242KZNA	SANTEC HD-CVI Full HD PTZ dome 5.1 - 61.2 mm motor zoom lens, IP-66
SCC-251KBIA	SANTEC HD-CVI Full HD IR bullet camera 2,8 - 11 mm mot. vario lens, IP-44
SCC-220KLNN	SANTEC HD-CVI Full HD box camera C/S Mount, 12 V DC / 24 V AC
VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter