



SCC-242KZNA

SANTEC HD-CVI Full HD PTZ dome
5.1 - 61.2 mm motor zoom lens, IP-66

PRODUCT DESCRIPTION

► Application:

SANTEC HD CVI speed dome for indoor and outdoor use according to IP-66.

► Technical specifications:

Type	HD-CVI speed dome
Video norm	HD-CVI, PAL
Sensor	1/2,8"
Sensor type	Exmor CMOS
Horizontal resolution (TVL)	1080p / 720p
Effective pixel	1920x1080
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	> 55dB
Lens type	Motor zoom lens
Focal length	5.1 - 61.2 mm / F1.6 - F3.0
Angle of view (horizontal)	51.3° - 4.64°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.05 lux (color) / 0.005 lux (B/W)
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/1 - 1/30,000
White balance	Auto / ATW / indoor / outdoor / manual
Backlight compensation	BLC, HLC, DWDR
Wide dynamic range (WDR)	DWDR

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



► Technical specifications:

Camera adjustments	OSD
Privacy zones	24
Video output	BNC, 75 Ohm 1 Vpp
Classification	IP-66
Vandal-proof	Yes, acc. to IK10
Installation	Surface mount
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	No
Voltage	24 V AC
Power consumption (watt)	max. 12
Operating temperature (°C)	-30 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxT (mm)	170 x 155
Weight	1.8 kg
Identifier	CE, RoHS
Specials	Coaxtransmission up to 700m

► Note:

1-channel BNC HDCVI high definition video output / CVBS standard definition video output (can switch).

► Recommended Accessories

SNCA-MK-4831	Adapter for SCC-242KZNA
SNCA-WM-4642	Wall mount bracket for SNC-211RSIA and SNCA-MK-4630 (SNC-311RDIA)
SNCA-JB-4640	Junction box for SNCA-WM-4642, SNCA-CM-4670 and SNCA-PM-4660
VCA-24V-1A/B	SANTEC power supply unit 24 V AC / 1 A