



## SCC-20KEIF

SANTEC 1080p HD-CVI mini IR dome camera  
3.6mm fix lens, 12V DC, IP-66

### PRODUCT DESCRIPTION

#### ► Application:

SANTEC day/night dome camera for indoor applications. Due to the built-in IR- LEDs (range: up to 20 m) and fix lens lens (3.6 mm), the camera is suitable for day as well as for night applications. The camera has an excellent resolution of 720p/25fps.

#### ► Technical specifications:

Type	Day/Night Dome camera
Video norm	HD-CVI
Sensor	1/2,8"
Sensor type	1/2.8" Progressive scan CMOS
Horizontal resolution (TVL)	1080p / 720p
Effective pixel	1920x1080
Signal processing	Digital (DSP)
Synchronisation	Intern
Lens type	Fixlens
Focal length	3.6 mm
Angle of view (horizontal)	69°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.05 / 0.0 Lux (IR-LED)
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/3 - 1/100,000
Video output	BNC, 75 Ohm 1 Vpp
Vandal-proof	No

SANTEC BW AG  
An der Strusbek 31, 22926 Ahrensburg, Germany  
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10  
info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

## ► Technical specifications:

Housing colour	White
Housing material	Plastic
Integrated IR-LEDs	Yes
IR range (m)	up to 30
Voltage	12 V DC
Power consumption (watt)	3.5
Operating temperature (°C)	-30 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxH (mm)	94 x 79.5
Weight	350 g
Identifier	CE, RoHS
Specials	Coaxtransmission up to 500m (1080p)

## ► Note:

The range of the built-in IR-LEDs strongly depend on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

## ► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring