



SCC-221KDNM

SANTEC HD-CVI Full HD dome camera
2,8 - 11 mm, manual vario lens, IP-44

PRODUCT DESCRIPTION

► Application:

SANTEC day/night HD-CVI dome camera for indoor applications.

► Technical specifications:

| | |
|-------------------------------|----------------------------|
| Type | Day/Night Dome camera |
| Video norm | HD-CVI, PAL |
| Sensor | 1/2.9" |
| Sensor type | 1/2.9" CMOS |
| Horizontal resolution (TVL) | 1080p / 720p |
| Effective pixel | 1920x1080 |
| Signal processing | Digital (DSP) |
| Synchronisation | Intern |
| Lens type | Built-in manual vario lens |
| Focal length | 2.8 - 11 mm / F1.4 |
| Angle of view (horizontal) | 103° - 22° |
| IR cut filter | IR-Cut filter (mechanical) |
| Sensitivity (Lux) | 0.05 Lux (color) |
| Automatic gain control (AGC) | AGC |
| Digital noise reduction (DNR) | 2NR / 3DNR |
| Shutter (sec.) | 1/3 - 1/100,000 |
| Video output | BNC, 75 Ohm 1 Vpp |
| Vandal-proof | No |
| Housing colour | White |
| Housing material | Plastic |

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

| | |
|----------------------------|-----------------------------|
| Integrated IR-LEDs | No |
| Voltage | 12 V DC / 24 V AC |
| Power consumption (watt) | 1.1 |
| Operating temperature (°C) | 0 to +45 |
| Rel. humidity (%) | Max. 95, non-condensing |
| Dimensions DxH (mm) | 128 x 90 |
| Weight | 270 g |
| Identifier | CE, RoHS |
| Specials | Coaxtransmission up to 700m |

► Note:

Caution: This camera must not be powered with multi-power supply adapters.

► Recommended Accessories

| | |
|----------------|---|
| VCA-12V-1.5ASA | SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter |
| KOAX-0.6/100 | Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring |
| SNPS-12D2 | SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter |