



SCVR-2812TK-2TB

SANTEC 8-channel digital video recorder
for HD-CVI, 1080p, incl. 2TB HDD

PRODUCT DESCRIPTION

► Application:

This tribrid digital video recorder of the SCVR series is able to record video signals of HD-CVI cameras as well as analogue cameras - in real-time at 25 fps on every channel in full resolution (up to 1080p resp. 960H). The recorder is also able to process images of max. 2 IP cameras (replacing the respective HD- CVI/analogue channels). The recorder is network-capable and has manifold functions such as integrated motion detection, camera signal detection or recording by schedule. Moreover, several recorders can be managed using an administration software. The recorder can remotely be accessed by the BURG CAM App.

► Technical specifications:

| | |
|--------------------------------|---|
| Type | Digital video recorder, HD-CVI 720p / 1080p |
| Video inputs | 8 x BNC 1Vpp |
| Video outputs | No |
| IP video channels (extendible) | 2 (optional) |
| Audio inputs | 4 x Cinch |
| Audio outputs | 1 x Cinch |
| Alarm inputs | 16 |
| Alarm outputs | 3 |
| HDD capacity (internal) | 2 TB |
| Max. HDD capacity | 8 TB |
| Max. number of HDDs (internal) | 2 x SATA |
| External HDD possible | through USB |
| RS-232 interface | Yes |
| RS-422 interface | No |
| RS-485 interface | Yes |
| USB interface | USB 2.0 |

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



► **Technical specifications:**

| | |
|------------------------------|----------------------------------|
| USB ports | 1 x Front, 1 x Backside |
| Ventilation | Fan |
| Monitor outputs | 1x VGA, 1 x HDMI |
| Spot monitor outputs | No |
| Internal RAID | Yes |
| Export interface | USB/network |
| Control panels (external) | PC-mouse |
| Remote control | IR Remote control |
| Number of Ethernet ports | 1 |
| Ethernet connector | RJ-45 |
| Ethernet speed | 10 / 100 Mbit |
| Ethernet standards | 10Base-T/100Base-TX |
| Video norm | HD-CVI, PAL |
| Compression (video) | H.264 |
| Compression (audio) | G.711 |
| Max. resolution | Full HD (1920x1080) |
| Max. frame rate (fps) | 25 fps |
| Alarm recording | Yes |
| Motion recording | Yes |
| Manual recording | Yes |
| Permanent recording | Yes |
| Schedule recording | Yes |
| Live picture | Yes |
| Mega pixel camera support | Yes |
| Play back mode | 4 channel / full screen |
| Motion detection | Yes |
| Lost signal detection | Yes |
| Picture data export | USB / network |
| Password protection | Yes |
| Log files | Yes |
| Supported OS | Mac OS X **, Windows Vista, 7, 8 |
| Management of IP devices | Yes |
| DynDNS support | Yes |
| PTZ control | No |
| Remote connections | Yes |
| User management | Yes |
| ONVIF/PSIA | ONVIF |
| Time synchronisation | Yes |
| DHCP support | Yes |
| Menu languages | Multi language |
| Access | Browser / Client SW / Mobile App |
| BURG-WÄCHTER cloud | Yes |
| Transmission speed (network) | max. 100 Mbit/S. |
| Firmware upgrade | Network / USB |

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 info@santec-video.com, www.santec-video.com



► Technical specifications:

| | |
|----------------------------|--|
| Noise emission (dB) | 50 |
| Housing colour | White |
| Power consumption (watt) | 15 (without HDD) |
| Voltage | 12 V DC using external power supply |
| Operating temperature (°C) | -10 to +55 |
| Rel. humidity (%) | Max. 95, non-condensing |
| Dimensions WxHxD (mm) | 376 x 56 x 285 |
| Weight | 2.23 kg (w/o HDD) |
| Identifier | CE, FCC, RoHs |
| Items included in delivery | Power supply, Mouse, IR remote control |

► Recommended Accessories

| | |
|----------------|--|
| SANSTORE-STICK | 4GB USB stick to backup recorded data |
| SCC-10KBIF | SANTEC 720p HD-CVI IR Outdoor Camera, 3.6mm Fixlens, IR-LED 20m, 12 V DC |
| KOAX-0.6/100 | Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring |