



HDCVI-810

PoC Transceiver
for HD-CVI / HDTV / AHD / CVBS, without PS.

PRODUCT DESCRIPTION

► Application:

Single cable coaxial transmitter and receiver for transmission of 1 video signal as well as 1 audio signal and 12 V DC for the camera. The power supply is included in the delivery.

► Technical specifications:

Type	Single cable coax Transceiver/Receiver
Video inputs	1 x BNC 1Vpp
Video outputs	1 x BNC 1Vpp
Splitter	no
Adjustable video level	no
Video norm	HDCVI, CVBS
S/N ratio (dB)	>60db
Housing material	Metal
Housing colour	Black
Voltage	24V-36V DC using external power supply
Cable type	Videocable RG-59 / RG-6
max. linkdistance	400m
Operating temperature (°C)	-10 to +55
Storage temperature (°C)	-20 to +70
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxHxD (mm)	29x22x78
Weight per 100m (kg)	153g
Identifier	CE
Specials	Video / Audio and Voltage using coax line

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Note:

The needed power supply is not in the delivery!

► Recommended Accessories

VCA-36V-1.67A

Stabilized power supply unit, 100-240 V AC 36 V DC, 1,67 A