



SNC-3322

SANTEC 2 MP Full HD IP-Motorzoomcamera
Day/Night, 18x optical zoom, PoE, 12/24 V

PRODUCT DESCRIPTION

► Application:

The SANTEC IP motor zoom camera has impressive image quality with 2 mega pixel resolution (1080p), 18x motor zoom lens and day/night function with mechanical IR cut filter. Functions such as wide dynamic range (WDR), Quadstreaming, Region of Interest (ROI), PoE and micro-SD card slot make the camera versatile which can be used for indoor and outdoor applications in combination with suitable weather-proof housings for almost every possible application.

► Technical specifications:

Type	IP motorzoom box camera
Sensor type	Progressive scan CMOS
Picture resolution (pixel)	Max. 2 MP (1920x1080)
Video codec	H.264 / MJPEG
Max. frame rate (fps)	25 at 2 MP (1920x1080)
Number of video streams	4 (individually adjustable)
Lens mount	Intern
Iris control	DC
Lens type	Int. 18x motorzoom
Focal length	4.7 - 84.6 mm
Angle of view (horizontal)	61° - 4°
Sensitivity (Lux)	0.2 (Color) / 0.02 (B/W)
IR cut filter	IR-Cut filter (mechanical)
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	3DNR, SPQ

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



► **Technical specifications:**

Shutter (sec.)	1 - 1/10000
White balance	AWB / ATW / manual
Backlight compensation	BLC
Wide dynamic range (WDR)	4 levels, digital
Digital zoom	Yes
Mirroring (vertical)	Yes
Privacy zones	Yes (5)
Region of Interest (ROI)	Yes
Camera title	Yes
Video output	BNC, 75 Ohm 1 Vpp
Audio support	Two-way
Audio in-/outputs	1 / 1 (3.5 mm phone jack)
Audio codec	G.711 / G.726
Alarm contacts I/O	1 / 1
RS-485 interface	Yes
Alarm management	HTTP, FTP, SMTP
Schedule	Yes
Management software support	Many VMS
Security features	HTTPS, IP Filter, IEEE 802.1X
Supported protocols	UPNP, BONJOUR, DHCP, FTP, HTTP, SMTP, RTSP
Supported software standards	ONVIF
Internal memory	Micro SDHC card (optional)
Video Content Analytics (VCA)	No
Ethernet connector	RJ-45
Ethernet standards	10Base-T/100Base-TX
Classification	IP-44
Housing colour	White
Housing material	Aluminium
IR distance (m. ca.)	no IR-LED
Voltage	12 V DC / 24 V AC / PoE
PoE standard	IEEE 802.3af
Power consumption (watt)	8
Operating temperature (°C)	0 to +40
Storage temperature (°C)	-10 to +50
Rel. humidity (%)	10 - 90, non-condensing
Dimensions WxHxD (mm)	80x52x184
Weight	500 g
Identifier	CE, RoHS
Items included in delivery	Quick install guide, manual on CD

► **Note:**

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

SD card is not included.

► **Weitere Bilder:**



► **Recommended Accessories**

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
VA-13WIK	Wall bracket for indoor metal, beige
VA-13WIK/10	Set 10pcs. wall brackets VA-13WIK wall bracket for indoor
HEL-IR65D	SANTEC weather-proof housing IP-66 IR-LEDs up to 70 m
HPV42K2A700	Videotec Housing with IPM Module Camera Housing for IP-cameras
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.