



## SNC-211FDIA

2 MP Full HD IP dome camera  
2.7 - 12mm mot. lens, IP-66, PoE

### PRODUCT DESCRIPTION

#### ► Application:

SANTEC SNC-211FDIA is a dome camera suitable for indoor as well as outdoor applications, including integrated IR LEDs. Hence the camera produces excellent images even at night or under poor light conditions. This IP camera has a weather-proof housing (IP-66) and is vandal-proof (IK10). Thanks to 2 megapixel resolution, the images are very clear hence no detail is undetected. Thanks to the motorized lens and the web interface the camera is easy to adjust. The camera comes with features such as 3DNR for noise reduction, Wide Dynamic Range (WDR) and PoE, to name but a few. Data can be stored and exported to a SD card (memory card not included in the delivery). You can also access this camera remotely, i.e. by using the Burg Cam App or by embedding in into the Burg-Wächter cloud.

#### ► Technical specifications:

Type	IP day/night dome camera
Sensor type	1/3" Progressive Scan CMOS
Picture resolution (pixel)	2 MP (1920x1080)
Video codec	H.264 / MJPEG
Max. frame rate (fps)	25 fps at 1080p
Number of video streams	2
Lens mount	Intern
Iris control	DC
Lens type	Motorized lens
Focal length	2.7 - 12 mm
Sensitivity (Lux)	0.01 Lux, F1.4
IR cut filter	IR-Cut filter (mechanical)
Day/night mode adjustment	Auto / color / B/W

SANTEC BW AG  
An der Strusbek 31, 22926 Ahrensburg, Germany  
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10  
info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Digital noise reduction (DNR)	3DNR
White balance	AWB
Backlight compensation	120 dB True WDR, BLC, HLC
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Privacy zones	4
Motion detection	Yes
Camera title	Yes
Management software support	Many VMS
BURG-WÄCHTER cloud	Yes
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP, UDP, UPNP, BONJOUR, DHCP, FTP, SMTP, RTSP
Supported software standards	ONVIF Profile S
Internal memory	Micro SDHC card (optional)
Ethernet connector	RJ-45
Ethernet standards	10Base-T/100Base-TX
Classification	IP-66
Vandal-proof	Yes, acc. to IK10
Heater	No
Installation	Wall and ceiling mount
Housing colour	White
Housing material	Metal / Plastic
Integrated IR-LEDs	Yes
IR distance (m. ca.)	20
Voltage	12 V DC, PoE
PoE standard	IEEE 802.3af
Power consumption (watt)	7.5
Operating temperature (°C)	-20 to +60
Storage temperature (°C)	0 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxH (mm)	122 x 89
Weight	500 g
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide

► **Note:**

SD card is not included. The range of the built-in IR-LEDs strongly depend on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt) may lead to a considerable reduction of the maximum range. This camera will be available again in December 2016.

### ► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
SNCA-WM-4644	wall bracket for SNC-431FEIF, 211FDIA, SCC-241KDIA, SNC-231RZNA
SNCA-MK-4631	Adapter / mounting kit for SNC-211FDIA and SNC-231RZNA
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm