



SNC-5323IR

SANTEC 3MP IP-bullet IR-camera
3x AF-zoom lens, IP-66, IR-LED, PoE

PRODUCT DESCRIPTION

► Application:

SANTEC IP outdoor camera SNC-5323IR with integrated IR-LEDs is the perfect solution for all 24/7 outdoor applications. Thanks to its 2 mega pixel (1080p) resolution and the integrated IR-LEDs, the camera delivers detailed and brilliant pictures in real-time at all times. The integrated DC 3x autofocus lens with 3-9 mm can be controlled by the webinterface. The slim camera design and the comprehensive set of accessories enable installations almost everywhere.

► Technical specifications:

Type	IP Day/Night bullet camera
Sensor type	1/2.8" 3.1 MP Sony progressive scan CMOS
Picture resolution (pixel)	3 MP (2048x1536)
Video codec	H.264 / MJPEG
Max. frame rate (fps)	15@3 MP, 25@2MP (Full HD)
Number of video streams	4 (individually adjustable)
Lens mount	Intern
Iris control	DC
Lens type	3x autofocus lens
Focal length	3 - 9 mm / F1.2
Angle of view (horizontal)	31°-95°@3MP, 28°-90°@2MP
Sensitivity (Lux)	0.2 (Color) / 0.02 (B/W) / 0.00 (IR-LED)
IR cut filter	IR-Cut filter (mechanical)
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	3DNR, SPQ

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



► Technical specifications:

Shutter (sec.)	1 - 1/10000
White balance	AWB / ATW / manual
Backlight compensation	BLC, WDR
Wide dynamic range (WDR)	4 levels, digital
Digital zoom	Yes
Mirroring (vertical)	Yes
Privacy zones	Yes (5)
Region of Interest (ROI)	Yes
Camera title	Yes
Video output	BNC, 75 Ohm 1 Vpp
Audio support	Two-way
Audio in-/outputs	1 / 1 (3.5 mm phone jack)
Audio codec	G.711 / G.726
Alarm contacts I/O	1 / 1
Alarm management	HTTP, FTP, SMTP
Schedule	Yes
Management software support	Many VMS
Security features	HTTPS, IP Filter, IEEE 802.1X
Supported protocols	UPNP, BONJOUR, DHCP, FTP, HTTP, SMTP, RTSP
Supported software standards	ONVIF
Internal memory	Micro SDHC card (optional)
Video Content Analytics (VCA)	No
Ethernet connector	RJ-45
Ethernet standards	10Base-T/100Base-TX
Classification	IP-66
Vandal-proof	No
Heater	No
Installation	Wall mount bracket included
Housing colour	RAL 9020 (matt white)
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR-LED illuminant	23
IR illumination angle (horizontal)	80 °
IR distance (m. ca.)	max. 25
Voltage	12 V DC / 24 V AC / PoE
PoE standard	IEEE 802.3af
Power consumption (watt)	11.6
Operating temperature (°C)	-20 to +50
Storage temperature (°C)	-20 to +60
Rel. humidity (%)	10 - 90, non-condensing
Dimensions WxHxD (mm)	92x88x296
Weight	1100 g
Identifier	CE, RoHS
Items included in delivery	Quick install guide, manual on CD

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 info@santec-video.com, www.santec-video.com



Note:

Eine SD-Karte ist nicht im Lieferumfang enthalten. Die Reichweite der IR- Strahler ist stark abhängig vom Einsatzort und von der Umgebung. Stark absorbierende Flächen, wie z.B. dunkle raue Strukturen (Boden, Rasen, Asphalt) können zu einer deutlichen Verringerung der maximalen Reichweite führen.

► **Weitere Bilder:**



► **Recommended Accessories**

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
VCA-12V-1.5AE	SANTEC stabilized power supply unit 12 V DC, 1.5A , for intergration
CMP-220W	Corner and mast mount adatper for SANTEC cameras incl. stainles steel clamps
JB-500	SANTEC Junction Box for cameras for WB-HDH (WB-HDHW) & SANTEC cameras
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter