



VTC-279IRHWD

SANTEC day/night bullet type IR-cam., 700 TVL, WDR
700TVL/960H, 2,8-12 mm, IR-LED, IP-66, 12/24 V

PRODUCT DESCRIPTION

► Application:

SANTEC compact colour camera for indoor and outdoor applications, IP-66. Due to the built-in IR-LEDs the camera is suitable for day as well as for night applications. The camera features a 3x vario lens, high resolution of 700 TVL / 960H, mechanical IR cut filter and WDR function. All adjustments can be made from outside, thus no need to open the camera.

► Technical specifications:

Type	Day/Night bullet camera
Video norm	PAL
Sensor	1/3"
Sensor type	Sony Super HAD II CCD Chip
Horizontal resolution (TVL)	700 (color) / 700 (b/w)
Effective pixel	976 (H) x 582 (V)
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	> 52 dB
Lens mount	Intern
Iris control	DC
Lens type	Manual zoom lens
Focal length	2.8 - 12 mm / F1.0
Angle of view (horizontal)	84° - 23°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0.05 / 0.0 Lux (IR-LED)
Automatic gain control (AGC)	AGC

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



► Technical specifications:

Digital noise reduction (DNR)	Yes
Backlight compensation	BLC, HLC, DWDR
Wide dynamic range (WDR)	Yes
Day/night mode adjustment	Auto / color / B/W
Camera adjustments	OSD, multi language
Digital zoom	No
Image stabilisation	Yes, digital
Mirroring (vertical)	Left, right
Picture flip (horizontal)	Top/bottom
Motion detection (zones)	4
Privacy zones	8
Camera title	15 characters
Video output	BNC, 75 Ohm 1 Vpp
UTP (twisted pair)	No
Control interface	No
Control protocols	Pelco P/D
Classification	IP-66
Heater	Yes
Housing colour	RAL 9020 (matt white)
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR range (m)	up to 40
IR illumination angle (horizontal)	50 °
IR illumination angle (vertical)	50 °
IR wave length	850
IR-LED illuminant	48
Voltage	12 V DC / 24 V AC
Power consumption (watt)	9.6
Operating temperature (°C)	-20 to +50
Rel. humidity (%)	30 - 90
Dimensions WxHxD (mm)	82 x 78 x 260
Weight	1050 g
Identifier	CE

► Note:

The range of the built-in IR-LEDs strongly depend on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► Weitere Bilder:

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.



► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
VCA-24V-8A16P	SANTEC 24 V AC Multiple power supply 24 V AC / 8A, 16 PTC-fused screwd outputs
JB-500	SANTEC Junction Box for cameras for WB-HDH (WB-HDHW) & SANTEC cameras
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter