



VTC-HDH210FSP

SANTEC vandal-proof color dome camera
580 TVL, surface/flush mount, 3.0mm lens

PRODUCT DESCRIPTION

► Application:

The vandal-proof dome camera has specially been developed for applications in public areas such as subway stations, elevators, public parking buildings, banks etc. The camera is designed for surface mount or flush mount.

► Technical specifications:

Type	Day/Night vandal-proof dome camera
Video norm	PAL
Sensor	1/3"
Sensor type	Sony Super HAD CCD Chip
Horizontal resolution (TVL)	580 (color) / 580 (b/w)
Effective pixel	752 (H) x 582 (V)
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	> 48 dB
Lens type	Fix lens
Focal length	3 mm / F2.0
Angle of view (horizontal)	77°
IR cut filter	Electronic
Sensitivity (Lux)	0.1 Lux
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	Yes
Backlight compensation	BLC
Wide dynamic range (WDR)	No
Day/night mode adjustment	Auto

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Motion detection (zones)	12
Camera title	No
Video output	BNC, 75 Ohm 1 Vpp
UTP (twisted pair)	No
Control interface	No
Classification	IP-66
Vandal-proof	Yes
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	No
Voltage	12 V DC
Power consumption (watt)	4
Operating temperature (°C)	-10 to +50
Rel. humidity (%)	30 - 90
Dimensions DxH (mm)	83x70
Weight	400 g
Identifier	CE

► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
----------------	---