



VDC-295AIODH-WBJB

SANTEC outdoor colour d/n speed dome
22x motor zoom, 3.9 - 85.8 mm, 24V AC

PRODUCT DESCRIPTION

► Application:

The SANTEC dome cameras are high speed domes in compact housings with integrated motor zoom lens. The domes are programmable for different features. Ideal applications are locations with fast movements. This dome camera is part of a set and comes with bracket WBJB-HDH-306.

► Technical specifications:

Type	Day/night speed dome
Video norm	PAL
Sensor	1/4"
Sensor type	Sony Super HAD II CCD Chip
Horizontal resolution (TVL)	700 / 960H
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	> 50 dB
Lens type	Motor zoom lens
Focal length	3.9 - 85.8 mm
Optical zoom	22x, adjustable
Digital zoom	16x, adjustable
Zoom range (opt./dig.)	22x / 16x
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	1.0 / 0.02 lux
Automatic gain control (AGC)	AGC
White balance	automatic
Backlight compensation	BLC

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
info@santec-video.com, www.santec-video.com



► Technical specifications:

Wide dynamic range (WDR)	Yes
Camera adjustments	OSD
Picture flip (horizontal)	No
Privacy zones	8
Preset positions	240
Auto scan	16
Tours	8
Pattern	8
Rotation radius	360°
Rotation speed	variable 0.1°/s. to 380°/s.
Preset speed	380°/S.
Tilt angle (°)	-10° to 190° (Digital flip)
Automatic calibration	0.1° ~ 6°
Camera addressing	up to 999 addresses
Video output	BNC, 75 Ohm 1 Vpp
Switch input contacts	4
Switch output contacts	1
Control interface	RS-485
Control protocols	Pelco P/D
Classification	IP-66
Housing colour	Beige
Housing material	Metal
Voltage	230 V AC
Power consumption (watt)	55
Operating temperature (°C)	-40 to +50
Dimensions WxHxD (mm)	234 x 278

► Recommended Accessories

HCM-150	Corner adapter for WM-HD_306
HCM-151	Pole bracket for WM-HDH-306 for poles with 80 - 150mm diameter
AP-HDH-306	mounting plate for WBJB-HDH-306