

## SC-32



LED 

A 32" LED-Backlit surveillance display, with rapid response time supporting high brightness and contrast ratio, is ideal for security and control centre environments.

The SC-32 featuring 450 nits of brightness, 3000:1 contrast ratio and Full HD 1920 x1080 resolution, delivers clear images and colour performance. 4ms response time and quick signal-switching enable the effectiveness of surveillance control. Flexibility of VGA, HDMI, BNC and S-Video connections ensure smooth system integration. Comfortable wide viewing angle makes the SC-32 an ideal solution for security control applications.

- > FHD 1920 x 1080 resolution
- > Anti-Burn-in™ technology
- > Built-in Image Enhancer: 3D Comb Filter/Deinterlace/Noise Reduction
- > Versatile connectivity (VGA, HDMI, BNC in/out, S-Video, Audio in/out)
- > Looping BNC video inputs for multiple connections
- > Quick signal-switching time (<=0.8 sec.)
- > NTSC/PAL auto-detection
- > Selectable signal source
- > PC compatible
- > Built-in speakers
- > Auto-adjustment for optimal setting
- > VESA standard wall mount



# SC-32

## Specifications

## SC-32

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD
	Panel Size	31.5"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.364 mm
	Brightness	450 cd/m <sup>2</sup> (Typical)
	Contrast Ratio	3,000:1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	16.7M
	Response Time	4 ms (GTG)
<b>Horizontal Resolution</b>	TV Lines	625TVL (NTSC) 650TVL (PAL)
	<b>Frequency (H/V)</b>	H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
<b>Input</b>	Analogue	15-Pin D-Sub
	HDMI	HDMI
	CVBS	BNC x 1
	S-Video	4-Pin mini DIN
<b>Out</b>	CVBS	BNC x 1
<b>Audio</b>	Audio In	1 x stereo audio in for PC
	Audio Out	1 x stereo audio out
	Speaker	2W x 2
<b>Power</b>	Power Supply	Internal
	Power Requirements	100 ~ 240V, 50 - 60Hz
	Consumption	< 65 W (On)
<b>Plug &amp; Play</b>	VESA	EDID
<b>Operating Conditions</b>	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
<b>Storage Conditions</b>	Temperature	-10 °C ~ 50 °C
	Humidity	10% ~ 95%
<b>Mounting</b>	VESA FPMPMI	Yes (200 x 100mm)
<b>Dimensions</b>	Product (W x H x D)	752.5 x 503.8 x 189 mm (29.6" x 21.2" x 7.4")
	Packaging (W x H x D)	807 x 548 x 118 mm (31.8" x 21.6" x 4.6")
	<b>Weight</b>	Product Weight Packaged Weight
<b>Regulation Approval</b>	Certifications & Compliance	CE, FCC, RoHs, WEEE
<b>Accessories</b>	Supplied	User manual, Base assembly installation guide, Remote control with AAA batteries, power cord, 15-Pin D-Sub cable & audio cable, screw package



Stylish and slim design ideal for professional security environments



Built-in speakers enable more rigorous security monitoring



Looping BNC video inputs allow multiple display connections



Video versatility, including VGA, HDMI, S-Video and BNC In/Out