



SNC-4302

SANTEC 2 MP Full HD IP-Dome Camera
4 mm fixlens, PoE

PRODUCT DESCRIPTION

► Application:

SANTEC SNC-4302 is a mini dome camera equipped with a 4 mm fix-lens. This camera can be used for all applications where a nicely-looking and small camera is needed. Despite of its smallness, the camera delivers perfect pictures with 2 mega pixel (1080p) resolution. The main applications for this camera are indoor projects.

► Technical specifications:

Type	IP day/night mini dome
Sensor type	1/2.7" Progressive scan CMOS
Picture resolution (pixel)	Max. 2 MP (1920x1080)
Video codec	H.264 / MJPEG
Max. frame rate (fps)	25 at 2 MP (1920x1080)
Number of video streams	4 (ind. config.)
Lens mount	Intern
Iris control	DC
Lens type	Fix lens
Focal length	4 mm / F1.5
Angle of view (horizontal)	78°
Sensitivity	0.1 (Color)
IR cut filter	Electronic
Day/night mode adjustment	No
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	3DNR, SPQ
Shutter (sec.)	1 - 1/10000
White balance	AWB / ATW / manual
Backlight compensation	BLC

Tele Connect
Telekommunikatie B.V.
Franciscusweg 277, 1216 SG Hilversum
Tel.: +31 (35) 6282245, Fax: +31 (35) 6210885
info@teleconnect.nl, www.teleconnect.nl

► **Technical specifications:**

Wide dynamic range (WDR)	4 levels, digital
Digital zoom	Yes
Mirroring (vertical)	Yes
Motion detection	Yes
Privacy zones	Yes (5)
Region of Interest (ROI)	Yes
Tampering Alarm	Yes
Camera title	Yes
Video output	No
Audio support	Yes
Audio in-/outputs	1 / 0 (3.5 mm phone jack)
Audio codec	G.711 / G.726
Alarm contacts I/O	0 / 0
Alarm management	HTTP, FTP, SMTP
Schedule	Yes
Management software support	Many VMS
Security features	HTTPS, IP Filter, IEEE 802.1X
Supported protocols	UPNP, BONJOUR, DHCP, FTP, HTTP, SMTP, RTSP
Supported software standards	ONVIF
Internal memory	Micro SDHC card (optional)
Video Content Analytics (VCA)	No
Ethernet connector	RJ-45
Ethernet standards	10Base-T/100Base-TX
Classification	IP-44
Vandal-proof	Yes, acc. to IK7
Heater & Fan	Nein
Installation	Surface mount
Camera mounting	screw fastening
Housing colour	Beige
Housing material	Plastic
Integrated IR-LEDs	No
Wavelength IR-LED	n.a.
IR-LED illuminant	n.a.
IR distance (m. ca.)	no int. IR-LED
Voltage	PoE
PoE standard	IEE 802.3af
Power consumption (watt)	4
Operating temperature (°C)	-10 to +50
Storage temperature (°C)	-20 to +60
Rel. humidity (%)	10 - 90, non-condensing
Dimensions DxH (mm)	110x48
Weight	200 g
Certification	CE, RoHS
Items included in delivery	Quick install guide, manual on CD

Further images:



► Recommended accessories

SANPOWER-MS01

1-Port PoE Power Supply, 15.4 watt incl. power cord