



SNC-441RBIA

4MP IR-bullet,H.265(+),TrueWDR,video analysis,PoE
2,7-13,5 mm lens, IP66

PRODUCT DESCRIPTION

► Application:

SANTEC SNC-441RBIA is a 4 MP bullet camera with integrated IR-LEDs and it is the perfect solution for all 24/7 indoor and outdoor applications. This IP camera has a weather-proof housing (IP-66) and is vandal-proof (IK10). Thanks to 4 megapixel resolution, the images are very clear hence no detail is undetected. Due to the auto focus lens and the web interface the camera is easy to adjust. The camera comes with features such as 3DNR for noise reduction, Wide Dynamic Range (WDR), PoE and micro-SD card slot, to name but a few.

► Technical specifications:

Type	IP day/night dome camera
Sensor type	1/3" Progressive Scan CMOS
Picture resolution (pixel)	4 MP (2688x1520)
Video codec	H.264, H.265, MJPEG, H.264+, H.265+
Max. frame rate (fps)	25 fps@4MP
Number of video streams	3 (1x Main, 2x Sub)
Lens mount	Intern
Iris control	DC
S/N ratio (dB)	< 50dB
Lens type	4x autofocus lens
Focal length	2,7 - 13,5 mm / F1.4
Angle of view (horizontal)	100° - 35°
Angle of view (vertical)	54° - 20°
Sensitivity (Lux)	0,05lx (color)
Sensitivity (Lux)	0Lux (IR on)
IR cut filter	IR-Cut filter (mechanical)
Day/night mode adjustment	Auto / color / B/W

► **Technical specifications:**

Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/3 - 1/100,000
White balance	Auto / sunny / night / outdoor / manual
Backlight compensation	BLC, HLC, WDR(120dB)
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Digital zoom	16x, adjustable
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Privacy zones	Yes, 4 zones
Region of Interest (ROI)	Yes, 4 zones
IVA via ONVIF Motion	Yes
People counting	Yes
Heatmap	Yes
Tripwire	Yes
Intrusion	Yes
Tampering Alarm	Yes
Scene change	Yes
Missing / Added	Yes
Audio detect	Yes
Face detect	Yes
Motion detection	Yes, 4 zones
Camera title	Yes
Video output	Yes
Audio support	Yes
Audio in-/outputs	1 / 1
Audio codec	G.711a / G.711Mu / AAC / G.726
Alarm contacts I/O	2 / 1
Alarm management	HTTP, FTP, SMTP, ONVIF
Schedule	Yes
Management software support	Many VMS
Supported browser	Internet Explorer 11
BURG-WÄCHTER cloud	Yes
Smartphone App	BurgCam App
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP, TCP, NTP, IPv4, IPv6, DHCP, TELNET, ONVIF, FTP
Supported software standards	ONVIF, PSIA, CGI
Internal memory	Micro SD (optional), max. 128 GB
Video Content Analytics (VCA)	Tripwire, Intrusion, Face detect, etc.
Ethernet connector	RJ-45
Ethernet standards	10/100Base-T
Classification	IP-66
Vandal-proof	No
Heater	No
Installation	Wall and ceiling mount

► Technical specifications:

3 axis	yes
Camera mounting	Screw mounting
Housing colour	White
Housing material	Metal / Plastic
Integrated IR-LEDs	Yes, Smart IR, off, manual
Wavelength IR-LED	850 nm
IR-LED illuminant	4
IR distance (m. ca.)	50
DORI max. (Detect-Observe-Recognize-Identify)	208m - 83m - 41m - 20m
DORI min. (Detect-Observe-Recognize-Identify)	64m - 26m - 13m - 6.5m
Voltage	12 V DC, PoE
PoE standard	IEEE 802.3af
Max. Power consumption (watt)	<11,5
Operating temperature (°C)	-30 to +60
Storage temperature (°C)	0 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxHxD (mm)	95 x 95 x 280
Weight	1070 g
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide

► Note:

SD card is not included.

► Recommended Accessories

VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
SANPOWER-MS01L	1-channel PoE power supply 48V DC
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter
SNCA-MK-4530	Adapter / Junction box for SNC-311RBIA and SNC-431RBIA
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
SNCA-CM-4670	Corner Mount Adapter for SNCA-JB-4640, -WM-4642 (SNC-211RSIA)