



SFC-241KDIM-A

SANTEC 4 in 1 CVBS dome camera
2,7- 12mm, IP-66

PRODUCT DESCRIPTION

► Application:

SANTEC SFC day/night bullet camera for indoor and outdoor applications, IP-66 classification. Due to the built-in IR-LEDs (range: up to 30m) and the 6mm lens, the camera is suitable for day as well as for night applications. Resolution of 960H in CVBS mode.

► Technical specifications:

Type	Day/night IR dome camera
Video signal	CVBS (analogue)
Sensor	1/2.9" CMOS
Sensor type	Progressive scan CMOS
Resolution	960H
Effective pixel	1945(H) x 1097(V)
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	< 65dB
Lens mount	Intern
Iris control	Auto/manual
Lens type	DC vario lens
Focal length	2,7 - 12 mm / F1.4
Angle of view (horizontal)	67° - 17°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0,02 Lux (color) / 0,0 Lux (IR on)
Automatic gain control (AGC)	AGC
Digital noise reduction (DNR)	2D

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



► **Technical specifications:**

Shutter (sec.)	1/25 - 1/100.000
White balance	AWB / manual
Backlight compensation	BLC, HLC, WDR
Wide dynamic range (WDR)	DWDR
Day/night mode adjustment	Auto / manual
Camera adjustments	OSD -> recorder menu
Auto focus	No
Focus control	Manual
Optical zoom	4x, adjustable
Digital zoom	4x adjustable
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Motion detection (zones)	Yes (via recorder)
Privacy zones	Yes, 8 zones
Camera title	Yes
Video output	BNC, 75 Ohm 1 Vpp
Switch input contacts	No
Switch output contacts	No
Control interface	No
Classification	IP-66
Vandal-proof	Yes, acc. to IK10
Installation	Wall mount, ceiling mount and pole mount
Camera mounting	Screw mounting
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR range (m)	up to 30
IR wave length	850
Voltage	12 V DC
Max. Power consumption (watt)	3,4
DORI max. (Detect-Observe-Recognize-Identify)	125m - 50m - 25m - 13m
DORI min. (Detect-Observe-Recognize-Identify)	49m - 20m - 10m - 5m
Operating temperature (°C)	-20 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions ØxH (mm)	122x88,9
Weight	0,4 Kg
Identifier	CE, FCC, RoHs, UL
Specials	Multi-norm: HDCVI, AHD, TVI, CVBS

► SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



Note:

The range of the built-in IR-LEDs strongly depends on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► Recommended Accessories

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter
VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
SNCA-MK-4631	Adapter / mounting kit for SNC-211FDIA and SNC-231RZNA
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
SNCA-WM-4644	wall bracket for SNC-431FEIF, 211FDIA, SCC-241KDIA, SNC-231RZNA
SNCA-ICM-PFB200C	Ceiling mount Suitable for: see recommended accessories
SFB-100	SFC controller switch for HD-CVI, AHD, TVI and CVBS