

# Digital IR Mini Bullet Camera



**Feature:**

- 1/3" High Sensitivity Image Sensor
- Ultra Hi-Resolution 600TVL
- Low Sensitivity 0Lux (LED off)
- Aspherical 3.6mm Lens
- Removable IR-CUT for true day and night performance
- Ultra Low Power Consumption ensures highest stability
- Constant Power Current Design ensures the utmost lifespan of LEDs
- 12pcs IR LEDs
- IP67 waterproof lever

**Installation:**

- To prevent shock or damage to the waterproof body, tighten all the screws and cover
- Adjust the visor to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol.
- Don't install it in the place where dithering and shake often
- Don't install it in the place where temperature is above 50°C or below -20°C
- Video line tie-in and DC tie-in must be avoided to touch water.
- If abnormal, please power off and contact the manufacturer

**Note: Non-regulated power supply may cause camera damaged.**

**Technical Specifications:**

Model No.	IV-CR8760FG	
Video System	NTSC/ PAL System	
Sensor	1/3" Hi-sensitivity image Sensor	
Numbers of Pixel	PAL: 762H×504V	
Resolution	600TVL	
Lens	Aspherical 3.6mm Lens	
Day & Night	CDS Control	
Sync.	Internal	
Scanning	2:1 Interlace	
Signal Noise Ratio	50dB Min.	
Electronic Shutter	PAL: 1/50-1/100,000S	
White Balance	Auto	
Backlight Compensation	OFF	
Auto Gain Control	ON	
Gamma Correction	0.45	
Video Output	1V p-p,75Ω	
IR LEDs	12LEDs	
Min. Illumination	0Lux (LED ON)	
IR Distance	10~15M (depend on scene reflection)	
Waterproof	IP67	
Voltage Input	DC12V±10%	
Power Current	LED OFF	70mA( Max.)
	LED ON	120mA (Max.)
Operation Temp.	-20°C~50°C	
Storage Temp.	-25°C~70°C	
Humidity Range	20%~90% RH	
Dimension	136L*57W*56H mm	
Net Weight	280g	