

Digital Color Mini UFO Camera



Feature:

- 1/3" Hi-sensitivity image Sensor
- Ultra Hi-Resolution 600TVL
- Low Sensitivity 0.00005Lux
- Aspherical 3.6mm Lens
- Ultra Low Power Consumption ensures highest stability
- Constant Power Current Design ensure the utmost lifespan

Installation:

- To prevent shock or damage to the waterproof body, tighten all the screws and cover
- Adjust the visor to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol.
- Don't install it in the place where dithering and shake often
- Don't install it in the place where temperature is above 50°C or below -20°C
- Video line tie-in and DC tie-in must be avoided to touch water.
- If abnormal, please power off and contact the manufacturer

Note: Non-regulated power supply may cause camera damaged.

Technical Specifications:

Model No.	IV-DC3060FG	
Video System	NTSC/ PAL System	
Sensor	1/3" Hi-sensitivity image Sensor	
Numbers of Pixel	NTSC: 768H*494V; PAL: 752H*582V	
Resolution	600TVL	
Lens	Aspherical 3.6mm Lens	
Day & Night	AUTO	
Sync.	Internal/ External	
Scanning	2:1 Interlace	
Signal Noise Ratio	48dB (Min.), 52dB (Max.)	
White Balance	ATW	
Backlight Compensation	On/ Off	
Auto Gain Control	On/ Off	
Gamma Correction	0.45	
Video Output	1V p-p,75Ω	
Min. Illumination	0.00005Lux	
Voltage Input	DC12V±10%	
Electronic Shutter	AES	NTSC: ON/ OFF (1/60s to 1/100000s); PAL: ON/ OFF (1/50s to 1/100000s)
	FIX	NTSC: 1/60~1/10,0000s; PAL: 1/50~1/10,0000s
Voltage Input	DC12V ±10%	
Power Current	80mA	
Operation Temp.	-20°C~50°C	
Storage Temp.	-25°C~70°C	
Humidity Range	20%~90% RH	
Dimension	ø64*58 mm	
Net Weight	250g	