

MOONLIGHT 600TVL Box Camera



Feature:

- 1/3" Sony Super HAD II CCD, Hitachi 14bit DSP
- Super High Resolution 600TVL
- Low illumination 0.00005Lux
- Removable IR-CUT
- Full OSD operation Controlled via RS485 or OSD joystick inside
- Can always remain in color in low light conditions
- Dual Power DC12V/ AC24V Optional

Installation:

- To prevent shock or damage to the waterproof body, tighten all the screws and cover
- Adjust the visor to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol.
- Don't install it in the place where dithering and shake often
- Don't install it in the place where temperature is above 50°C or below -20°C
- Video line tie-in and DC tie-in must be avoided to touch water.
- If abnormal, please power off and contact the manufacturer

Note: Non-regulated power supply may cause camera damaged.

Technical Specifications:

Model No.	IV-MS1060A
Video System	NTSC/ PAL System
Sensor	1/3" Sony Super HAD II CCD Hitachi 14bit DSP
Numbers of Pixel	NTSC: 768H*494V; PAL: 752H*582V
Resolution	600TVL(Color), 650TVL(B/W)
Lens	NONE
Day & Night	COLOR,B/ W (Saturation protection Erea Select), EXT, AUTO (D/ N LEVEL;LOW/ MIDDLE/ HIGH)
Sync.	Internal
Scanning	2:1 Interlace
Signal Noise Ratio	50dB Min.
Electronic Shutter	NTSC: 1/60-1/60,000S; PAL: 1/50-1/60,000S
White Balance	ATW/ MANUAL/ PUSH
Backlight Compensation	OFF, ON (ZONE ADJUSTABLE)
Auto Gain Control	Off/ On (0~20)
Gamma Correction	0.35/ 0.4/ 0.45/ 0.65/ 0.75 Selectable
Video Output	1V p-p,75Ω
Min. Illumination	0.00005Lux
Voltage Input	DC12/ AC24V
Power Current	250mA/ 120mA
Operation Temp.	-10°C~50°C
Storage Temp.	-20°C~60°C
Humidity Range	30%~80% RH
Dimension	118*64*64 mm
Net Weight	300g