960H Intelligent IR Eyeball Camera



Feature:

- 1/3" Sony Ex-View 960H CCD
- Aspherical 3.8-9mm Lens
- 36pcs Intelligent IR LEDs
- Ultra Low Power Consumption ensures highest stability
- Constant Power Current Design ensure the utmost lifespan of LEDs
- This intelligent IR camera has extreme variable infrared response and excellent low sensitivity, exceptional 700TV Lines, ensure optimal color by day, black and white by night, always generate the best possible picture from 30 centimeters to 40 meters away
- Optional OSD Menu on Cable Control or via OSD joystick.

Installation:

- To prevent shock or damage to the waterproof body, tighten all the screws and cover
- Adjust the visor to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol.
- Don't install it in the place where dithering and shake often
- Don't install it in the place where temperature is above 50°C or below -20°C
- Video line tie-in and DC tie-in must be avoided to touch water.
- If abnormal, please power off and contact the manufacturer

Note: Non-regulated power supply may cause camera damaged.

Technical Specifications:

Video System NTSC/ PAL System	Mar dal Nia		IV CDCE70ICO
Sensor	Model No.		IV-SR6570ISO
Numbers of Pixel NTSC: 976H*494V; PAL: 976H*582V Resolution 700TV Lines Lens Aspherical 3.8-9mm Lens Day & Night AUTO (CDS Control) Sync. Internal Scanning 2:1 Interlace Signal Noise Ratio 52dB Min. Electronic Shutter NTSC: 1/60-1/100,000S; PAL: 1/50-1/100,000S White Balance Auto Backlight Compensation On/ Off Auto Gain Control On/ Off Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Video System		• •
Resolution 700TV Lines Lens Aspherical 3.8-9mm Lens Day & Night AUTO (CDS Control) Sync. Internal Scanning 2:1 Interlace Signal Noise Ratio 52dB Min. Electronic Shutter NTSC: 1/60-1/100,000S; PAL: 1/50-1/100,000S White Balance Auto Backlight Compensation On/ Off Auto Gain Control On/ Off Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Sensor		1/3" SONY EX-View 960H CCD, Sony 4140 DSP
Lens Aspherical 3.8-9mm Lens Day & Night AUTO (CDS Control) Sync. Internal Scanning 2:1 Interlace Signal Noise Ratio 52dB Min. Electronic Shutter NTSC: 1/60-1/100,000S; PAL: 1/50-1/100,000S White Balance Auto Backlight Compensation On/ Off Auto Gain Control On/ Off Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Numbers of Pixel		NTSC: 976H*494V; PAL: 976H*582V
Day & Night AUTO (CDS Control) Sync. Internal Scanning 2:1 Interlace Signal Noise Ratio 52dB Min. Electronic Shutter NTSC: 1/60-1/100,000S; PAL: 1/50-1/100,000S White Balance Auto Backlight Compensation On/ Off Auto Gain Control On/ Off Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination OLux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) Power Current LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Resolution		700TV Lines
Sync. Scanning Scanning Scanning Scanning Signal Noise Ratio Signal N	Lens		Aspherical 3.8-9mm Lens
Scanning 2:1 Interlace Signal Noise Ratio 52dB Min. Electronic Shutter NTSC: 1/60-1/100,000S; PAL: 1/50-1/100,000S White Balance Auto Backlight Compensation On/ Off Auto Gain Control On/ Off Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) Departion Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Day & Night		AUTO (CDS Control)
Signal Noise Ratio 52dB Min.	Sync.		Internal
Electronic Shutter NTSC: 1/60-1/100,000S; PAL: 1/50-1/100,000S	Scanning		2:1 Interlace
White Balance Auto Backlight Compensation On/ Off Auto Gain Control On/ Off Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Signal Noise Ratio		52dB Min.
Backlight CompensationOn/ OffAuto Gain ControlOn/ OffGamma Correction0.45Video Output1V p-p,75ΩIR LEDs36 LEDsMin. Illumination0Lux (IR LEDs ON)IR Distance30~40MVoltage InputDC12V±10%Power CurrentLED OFF80mA(Max.)LED ON290mA (Max.)Operation Temp20°C~50°CStorage Temp25°C~70°CHumidity Range20%~90% RHDimensionΦ140*89 mm	Electronic Shutter		NTSC: 1/60-1/100,000S; PAL: 1/50-1/100,000S
Auto Gain Control On/ Off Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	White Balance		Auto
Gamma Correction 0.45 Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Backlight Compensation		On/ Off
Video Output 1V p-p,75Ω IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Auto Gain Control		On/ Off
IR LEDs 36 LEDs Min. Illumination 0Lux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Gamma Correction		0.45
Min. Illumination OLux (IR LEDs ON) IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Video Output		1V p-p,75Ω
IR Distance 30~40M Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	IR LEDs		36 LEDs
Voltage Input DC12V±10% Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Min. Illumination		0Lux (IR LEDs ON)
Power Current LED OFF 80mA(Max.) LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	IR Distance		30~40M
Power Current LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Voltage Input		DC12V±10%
LED ON 290mA (Max.) Operation Temp. -20°C~50°C Storage Temp. -25°C~70°C Humidity Range 20%~90% RH Dimension Φ140*89 mm	Power Current	LED OFF	80mA(Max.)
Storage Temp25°C~70°C Humidity Range 20%~90% RH Dimension Ф140*89 mm		LED ON	290mA (Max.)
Humidity Range20%~90% RHDimensionΦ140*89 mm	Operation Temp.		-20°C~50°C
Dimension Φ140*89 mm	Storage Temp.		-25°C~70°C
	Humidity Range		20%~90% RH
Net Weight 750a	Dimension		Ф140*89 mm
-3 -	Net Weight		750g