

4CH Full HD Digital Video Recorder



Feature:

- New Stylish Industrial Design, simple but elegant, easy to fit any installation environment;
- Adopt newest TI(Texas Instruments) high efficiency chipset;
- True Stand-alone Hardware H.264 Compression;
- Full HD 4CH 1080P Live Display/ Recording/ 1CH 1080P Playback;
- Support eSATA HDD Recording and Backup. Easy locate incident video, then transfer to external storage via USB, eSATA or Network
- Support HDMI output, maximum up to 1080P;
- Live viewing on 3G/4G-enabled Smartphones & tablets including
- iPhone, iPad, Android, Blackberry, Symbian etc. Remote notification via email
- Multi-language Interface easy to use.
- A cutting-edge solution for any home or business high standards application

Installation:

- To prevent shock or damage to the waterproof body, tighten all the screws and cover
- Adjust the visor to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol.
- Don't install it in the place where dithering and shake often
- Don't install it in the place where temperature is above 50°C or below -20°C
- Video line tie-in and DC tie-in must be avoided to touch water.
- If abnormal, please power off and contact the manufacturer

Note: Non-regulated power supply may cause camera damaged.

Technical Specifications:

Model No.	IV-DVR9240B	
System	CPU	TI (Texas Instruments) DM8167
	Operation System	Linux
Video	Video Compression	H.264 Mainprofile
	Video Preview Resolution	1080P
	Video Recording	PAL: 1080P @100fps; NTSC: 1080p@120fps
	Video Playback	NTSC: D1@120fps; PAL: D1@100fps (4cD1)
	Video Input	BNC*4, 4CH HD-SDI 1080P
	Video Output	1 CH VGA and 1CH HDMI, both Support 1080P
Audio	Audio Compression	8K*16bit ADPCM
	Audio Input	RCA , 4 channel
	Audio Output	RCA , 1 channel
Storage & Backu	HDD Port	2 SATA port, support up to 4000G
	Esata port	Support
	Backup Device	USB2.0 U disk/Network download
USB	USB Interface	2 USB 2.0 Ports
Alarm	IO Alarm	4 CH input, 1 CH output
	Video	Motion detection, Video loss detection, Temper detection
	Alarm Linkage	RS485 Recording, Buzzer, Email, FTP upload, Alarm Output, PTZ
Network	Network Port	1 RJ45 10M/100M Ethernet port
	Network Functions	Support TCP/IP, PPPoE, DHCP, DDNS, UPnP, SMTP, FTP
	Remote Control Tools	IE, CMS
	Mobile phone Live viewing	support Windows Mobile, Blackberry, iPhone, Android, Symbian
Power	Power Supply	DC 12V
Other	Dimension (mm)	405(W) * 58(H) * 325(D)
	Weight (without HDD)	4.0kg