

IP Starlight Bullet Camera



Feature:

- Support UPNP
- Support H.264, MJPEG compression
- Support G.711 audio compression
- Support two way audio, external audio input, output
- Support RTSP, VLC(PS/TS) Stream Media protocol
- Free management software support 1-200 channels
- Multi-level user access with password protection
- Alarm I/O support motion detection, date, time, event trigger
- Support WEB browser, remote config/update, replay, record

Installation:

- To prevent shock or damage to the waterproof body, tighten all the screws and cover
- Adjust the visor to prevent the lens from direct sunlight
- Do not directly touch the front glass. To clean the dust, wipe with soft cloth with alcohol.
- Don't install it in the place where dithering and shake often
- Don't install it in the place where temperature is above 50°C or below -20°C
- Video line tie-in and DC tie-in must be avoided to touch water.
- If abnormal, please power off and contact the manufacturer

Note: Non-regulated power supply may cause camera damaged.

Technical Specifications:

Model No.	IV-NT9011D
Image Sensor	1/3" SONY Super HAD II CCD 600TVL
Day/ Night	Auto
Lens	2.8-10mm
Min. Illumination	0.00001Lux
Auto Iris	Support
Scan System	Interlace

Video/ Audio	
Video Compression	H.264/ MJPEG
Frame Rate	1-30f/s
Resolution	D1, Half D1, CIF, QCIF
Video Stream	Bit-rate Range; 1M-8Mbps (H.264)/ 1M-20Mbps (MJPEG)
Image Setting	Brightness, Contrast, Saturation, Hue, Exposal Control, AES (1/2-1/4,000s), AGC, AWB, BLC, Privacy Mask, Motion Detection
Video H-REV	Support Horizontal Reverse
Video V-REV	Support Vertical Reverse
Audio Compression	G.711
Audio Stream	Two way Audio, Broadcast
Audio Input/ Output	Mic Input, Headphone output
Network	
UNP	Support
Mobile Veiwng	Support
Ethernet	10/100 Mbps, Ethernet RJ-45 port
Protocols	PPPOE, DHCP, TCP/ IP, HTTP, UDP, RTP/RTCP, RTSP, UPNP, SMTP, FTP, SI, DDNS, DNS
Security	Multi-level user access with password protection
System Integration	
IP Camera Hardware	CPU HI3512, FLASHI 8M, DRAM 128M, OS Built-in Linux
View System Requirement	OS: Microsoft Windows 2000/ 2003/ XP/ Vista/ Win7
	Browser: Internet Explorer 6.0 or above
Management Software	FREE software for monitoring and recording, support 1-100 channels
WEB Server	Support WEB Browser, Remote Config/ Update, Replay, Record
Alarm Port	1 External I/O Interface
Alarm Trigger	Video Lost, Motion Detection, External Input
Alarm Events	File upload via FTP, Email, Notification via Email, and TCP, External output activation, Local Recording
SDK	SDK Available for application development and system integration
General	
Local Storage	N/A
Connectors	RJ-45, 10BASE-T/ 100BASE-TX, DC Power, Terminal Block for 1 Alarm input, 1 output, MIC input headphone output, RS485 (PTZ), Alarm I/O, IRIS, SIM Slot
Operation Conditions	Temp. -10°C - 65°C; Humidity: <85%RH
Voltage	DC 12V
Dimension	216L*75W*73H mm
Net Weight	650g
Warranty	1 Year