SRECIFICATION S



SECURITY SYSTEMS

PROTECT 375XP



PROTECT 375XP SMOKE CANNON is suitable for small and medium size offices, shops, private homes etc.

- 60 sec. of smoke + 7 min. pulse
- Smoke production can be timed at 3 intervals from 125 - 375 m³
- · Quick and unproblematic replacement of intelligent fluid container. Now +40 % more smoke fluid without extra charge!
- · Built-in battery back-up (up to 3 hours)
- · Built-in automatic loading test of batteries







Intelligent smoke fluid container Possibility of 30° nozzle for all models

- · Extended battery life
- · Smart data display for quick and easy service and eventual trouble shooting
- · Can be mounted in any position
- · Possibility of 30 degree nozzle
- · Full integration to all alarm systems
- · Danish quality and design
- · Available in all colours

Specifications	PROTECT 375 ^{XP}
----------------	---------------------------

Performance (smoke generation)	375 m ³ /60 sec. (6,3 m ³ /sec.)
Total capacity, full container	App. 3055 m ³
Fluid container	1,1 litre
Mains connection	230 V, 50 Hz
Power consumption	1080 Watt
Standby consumption after heating up	65 Watt (on average)
Standby consumption when heat is disabled	5-10 Watt
Heating time from cold	15 minutes
Dimensions	L: 456, W: 340, H: 160 (mm)
Installation weight	13,4 kg
Inputs	5 signals
Outputs	3 signals
Battery back-up (2 x 12 V, 1.2 Ah)	Electronics and pumps
Control Settings	Dip switches
Signals / Indications	Optical, audible and electrical
Information Display	Smart Status Indicator
After smoke activation	Pulse
Data Log Memory	Optional

