

PROTECT 550



**NEW
PRODUCT**

PROTECT 550 SMOKE CANNON performs quickly and powerful and is designed for the larger offices and shops, smaller warehouses etc.

- 550 m³ smoke at 60 sec.
- Smoke production can be timed at 4 intervals from 140 – 550 m³.
- Quick and unproblematic replacement of intelligent fluid container.
- Built-in battery back-up (up to 3 hours)
- Built-in automatic loading test of batteries
- Extended battery life
- Smart data display for quick and easy service and eventual trouble shooting
- Can be mounted in any position
- Possibility of 30 degree nozzle
- Full integration to all alarm systems
- Danish quality and design
- Available in all colours



Intelligent smoke fluid container

Possibility of 30° nozzle for all models

A few seconds after a break-in

Specifications PROTECT 550

Performance (smoke generation)	550 m ³ /60 sec. (9,2 m ³ /sec.)
Total capacity, full container	App. 3055 m ³
Fluid container	1,1 litre
Mains connection	230 V, 50 Hz
Power consumption	1080 Watt
Standby consumption after heating up	65 Watt (on average)
Standby consumption when heat is disabled	5-10 Watt
Heating time from cold	21 minutes
Dimensions	L: 456, W: 340, H: 160 (mm)
Installation weight	16,6 kg
Inputs	5 signals
Outputs	3 signals
Battery back-up (2 x 12 V, 1.2 Ah)	Electronics and pumps
Control Settings	Dip switches
Signals / Indications	Optical, audible and electrical
Information Display	Smart Status Indicator
Time for re-heating after smoke activation	0-8 minutes
Data Log Memory	Optional



Protect is the most innovative company within the security smoke industry. The Danish-based company is now represented in more than 30 countries by professional dealers and distributors.

www.ProtectGlobal.com