

RC3502HD-5211

H.264 Full HD Outdoor Fixed Dome IP Camera

- Full Frame at HD1080p
- Video Compression: H.264, MJPEG
- Dual Stream
- Burnt-in Text, Video Motion Detection Support
- Two-way Audio with G.711
- microSD Memory Support
- Remote Firmware Upgrade over Network
- Comprehensive SDK Support
- Embedded Video Analytics (Planned for the future release.)




Specifications

Camera Module	
Image Sensor	1/2.7" 1080p CMOS
Effective Pixels	1920 x 1080
Scanning System	Progressive scanning
AGC Control	Auto
Minimum Illumination	Color: 1.0 lux, F1.2 BW: 0.1 lux, F1.2
Lens	3.0 – 9.0mm Vari-Focal F1.2
Day & Night	IR Cut Filter Removal
Video	
Compression Format	H.264, MJPEG
Number of Streams	Dual Stream, Configurable
Resolution	1920x1080, 1280x720, 800x450, 480x270, 320x180
Compression FPS	Configurable up to 30fps@1080HD
Motion Detection	Built-in
Burnt-in Text	Video stream overlay text
Output	Analog video output for installation only
Audio	
Input	1 channel
Output	1 channel
Compression Format	G.711
Function	
Digital Input	1
Digital Output	1
Network	10 / 100 Base-T
Protocol	TCP/IP, UDP/IP, HTTP, RTSP, RTCP, RTP/UDP, RTP/TCP, SNTP, mDNS, UPnP, SMTP, SOCK, IGMP, DHCP, DDNS, SSL v2/v3, IEEE 802.1X, SSH, SNMP v2/v3
SD Memory Card Slot	1
Electrical	
Power Source	12V DC
Power over Ethernet	Support (IEEE 802.3af)
Power Consumption (Approx)	400mA @ 12V DC
Environmental	
Fan / Heater	Fan and Heater
Operating Temperature	DC12V: -10 °C ~ 50 °C (14 °F ~ 122 °F) PoE: 0 °C ~ 50 °C (32 °F ~ 122 °F)
Operating Humidity	Up to 85% RH, Non-condensing
Mechanical	
Material	Aluminum Die Casting

Color	White
Dimension	Housing: 115(Φ) x 129(H) mm, Dome: 100(Φ) mm
Weight (Approx)	1.2kg

Dimension



(Unit: mm)