


RE40K-B

19", 4U Network Video Encoder Rack Solution

- Scalable Solution - up to 40 Video channels Per Rack
- 19" / 4U Aluminum Sub-Rack Support up to 10 Units of 4 channel Encoder Blades (Total 40 channel@D1)
- Hot-Swappable encoder Blades, Fan Units and Power Units
- Hardware Diagnostics Include Rack Chassis Identification
- Identification of Each Sub-Rack and Each Blade Unit (for Easy and Quick Maintenance)
- Detect Power Supplier Unit Operation (Self-Diagnosing)
- Detect Fan Unit Operation (Self-Diagnosing)
- Temperature Sensor Included
- Fault Tolerant Design




Specifications


Video Encoder Rack		
Rack Construction	Aluminum 19" / 4U Sub-Rack	
Available Slots	10 ea (Hot Swappable Blades)	
Power	Input	90~264 V AC, 47~63 Hz, 2A
	Type	Dual Power Supply (Hot Swappable)
Fan Unit	1,800 rpm x 3 ea (Hot Swappable)	
Temperature	0°C ~ 60°C (32°F ~ 140°F)	
Humidity	Up to 85% RH	
Dimension	482(W) x 177(H) x 325(D) mm	
Weight	6.90 kg + 380 g (NVC4000-R40) x 10 ea	
Power Consumption	Typically 140W Fully Loaded Rack	
Supported Blades	NVC4000-R40 (for 40 channel Rack)	

Dimension


(Unit: mm)




Rear View



Top View



Front View



Right Side View